



General Description	Product Summary
<ul style="list-style-type: none"> Trench Power SGT technology Very low on-resistance $R_{DS(ON)}$ Low Gate Charge Excellent Gate Charge x $R_{DS(ON)}$ Product 	V_{DS} 100V I_D (at $V_{GS}=10V$) 100A $R_{DS(ON)}$ (at $V_{GS}=10V$) < 8.2mΩ $R_{DS(ON)}$ (at $V_{GS}=4.5V$) < 9.5mΩ
Applications	100% UIS Tested
<ul style="list-style-type: none"> High Frequency Switching and Synchronous Rectification 	

TO-252		TO-220C		
Part Number	Package Type	Form	Marking	
HGS100N10C	TO-252	Tape&Reel	HGS100N10C	
HGS100N10C	TO-220C	Tube	HGS100N10C	
HGS100N10C	PDFN5*6		HGS100N10C	

Absolute Maximum Ratings ($T_A = 25^\circ C$ unless otherwise noted)

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ^B	I_D	90	A
$T_C = 100^\circ C$	I_D	76	
Pulsed Drain Current ^A	I_{DM}	380	A
Avalanche Current ^A	I_{AS}	38	A
Single Pulse Avalanche Energy $L = 0.3mH$ ^A	E_{AS}	300	mJ
Power Dissipation ^C	P_D	230	W
$T_C = 100^\circ C$	P_D	140	W
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Maximum	Units
Maximum Junction-to-Case	R_{eJC}	0.8	°C/W
Maximum Junction-to-Ambient	R_{eJA}	50	



Electrical Characteristics($T_J = 25^\circ\text{C}$ unless otherwise noted)						
Symbol	Parameter	Conditions	Value			Units
			Min	Typ	Max	
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D = 250\mu\text{A}, V_{\text{GS}} = 0\text{V}$	100			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}} = 100\text{V}, V_{\text{GS}} = 0\text{V}$	$T_J = 25^\circ\text{C}$		1	μA
			$T_J = 125^\circ\text{C}$		100	
I_{GSS}	Gate-Body Leakage Current	$V_{\text{DS}} = 0\text{V}, V_{\text{GS}} = \pm 20\text{V}$			± 100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250\mu\text{A}$	1.1	1.6	2.4	V
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}} = 10\text{V}, I_D = 30\text{A}$		6	7	$\text{m}\Omega$
		$V_{\text{GS}} = 4.5\text{V}, I_D = 30\text{A}$		8	9	$\text{m}\Omega$
g_{FS}	Forward Transconductance	$V_{\text{DS}} = 5\text{V}, I_D = 20\text{A}$		80		S
V_{SD}	Diode Forward Voltage	$I_S = 30\text{A}, V_{\text{GS}} = 0\text{V}$			1	V
I_s	Maximum Body-Diode Continuous Current ^B				100	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 50\text{V}, f = 1\text{MHz}$		3000		pF
C_{oss}	Output Capacitance			530		
C_{rss}	Reverse Transfer Capacitance			20		
R_g	Gate Resistance	$f = 1\text{MHz}$		0.9		Ω
SWITCHING PARAMETERS						
$Q_g(10\text{V})$	Total Gate Charge	$V_{\text{GS}} = 10\text{V}, V_{\text{DS}} = 50\text{V}, I_D = 20\text{A}$		25.7		nC
$Q_g(4.5\text{V})$	Gate Source Charge			13		
Q_{gs}	Gate Source Charge			4.3		
Q_{gd}	Gate Drain Charge			5.3		
Q_{oss}	Output Charge			34.2		
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{\text{GS}} = 10\text{V}, V_{\text{DS}} = 50\text{V}, I_D = 20\text{A}, R_G = 1.8\Omega$		33		ns
t_r	Turn-On Rise Time			4		
$t_{\text{D(off)}}$	Turn-Off Delay Time			55		
t_f	Turn-Off Fall Time			3.1		
t_{rr}	Body Diode Reverse Recovery Time			49		ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_F = 20\text{A}, \text{di/dt} = 100\text{A}/\mu\text{s}$		71		nC

- A. Single pulse width limited by maximum junction temperature.
- B. The maximum current rating is package limited.
- C. The power dissipation P_D is based on $T_{J(\text{MAX})} = 175^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current




Figure 4: Capacitance Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Body Diode Forward Voltage



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS











Figure A: Gate Charge Test Circuit and Waveforms




Figure B: Resistive Switching Test Circuit and Waveforms






Figure C: Unclamped Inductive Switching (UIS) Test Circuit and Waveforms





TO-252




Unit: mm			
Symbol	Min	Nom	Max
A	2.20	2.30	2.38
A1	0.00	-	0.10
A2	0.90	1.01	1.10
b	0.72	-	0.85
b3	5.13	5.33	5.46
c	0.47	-	0.60
D	6.00	6.10	6.20
D1	5.25 REF		
E	6.50	6.60	6.70
E1	4.70	-	-

Unit: mm			
Symbol	Min	Nom	Max
e		2.286BSC	
H	9.80	10.10	10.40
L	1.40	1.50	1.70
L1	2.90REF		
L2	0.508BSC		
L3	0.90	-	1.25
L4	0.60	0.80	1.00
L5	1.8 REF		
Θ	0°	-	8°
Φ			



TO-220C



Unit: mm		
Symbol	Min.	Max.
A	4.37	4.77
A1	1.25	1.45
A2	2.20	2.60
b	0.70	0.95
b2	1.17	1.47
c	0.40	0.65
D	15.10	16.10
D1	8.80	9.40
D2	5.50	-

Unit: mm		
Symbol	Min.	Max.
E	9.70	10.30
E3	7.00	-
e	2.54BSC	
e1	5.08BSC	
H1	6.25	6.85
L	12.75	13.80
L1	-	3.40
P	3.40	3.80
Q	2.60	3.00